

DGT Conduflex Drag Chains (SUS430)



Material: Plastic PA66 and Stainless steel 430




Approvals : CE, ISO

Structure : Rectangle Total Enclosed Cable Drag Chain

Color : Silver, Natural

Temperature Resistance : -40°C to 125°C

Size Dimension

Type	Inside	Outside	Non-Support Length (M)	Bendind Radius			
	Height x Width	Height x Width			A End Bracket	B End Bracket	C End Bracket
DGT	25 x 48	39 x 62	1.5	75	4,200.-	สอบตาม	สอบตาม
	38 x 73	53 x 91	2	100	4,600.-	สอบตาม	สอบตาม
	45 x 90	61 x 108	2.2	130	5,000.-	สอบตาม	สอบตาม
	52 x 102	70 x 122	2.5	150	5,400.-	สอบตาม	สอบตาม
	60 x 120	81 x 144	2.7	165	6,400.-	สอบตาม	สอบตาม
	60 x 150	81 x 184	2.9	165	7,800.-	สอบตาม	สอบตาม
	72 x 162	93 x 186	3	185	9,980.-	สอบตาม	สอบตาม

JR-2 Rectangle Drag Chain



Material: Steel and stainless




Approvals : CE, ISO

Structure : Rectangle Total Enclosed Cable Drag Chain

Color : Silver, Natural

Temperature Resistance : -40°C to 125°C

Size Dimension

Type	Inside	Outside	Weight (Kg/m.)	Bendind Radius			
	Height x Width	Height x Width			A End Bracket	B End Bracket	C End Bracket
JR-2	22 x 32	27.5 x 36.7	1.3	60	3900.-	สอบตาม	สอบตาม
	25 x 50	31.5 x 54.5	1.75	90	4300.-	สอบตาม	สอบตาม
	35 x 60	40.1 x 64.4	2.1	100	4700.-	สอบตาม	สอบตาม
	38 x 73	43.7 x 77.8	2.36	110	4950.-	สอบตาม	สอบตาม
	40 x 80	45.4 x 84.7	2.5	120	5380.-	สอบตาม	สอบตาม
	52 x 102	57.5 x 107.8	2.85	140	5900.-	สอบตาม	สอบตาม
	60 x 120	67.5 x 127.7	3.15	180	6500.-	สอบตาม	สอบตาม
	60 x 130	65.1 x 134.4	3.25	180	7200.-	สอบตาม	สอบตาม
	72 x 162	78.4 x 168.2	4.5	210	8400.-	สอบตาม	สอบตาม

